

## We call it 'Non-Powered, Powered Access'

As part of the Eco range the EcoLift still harnesses the same Eco friendly revolutionary 'Patented Stored Power System' as the PecoLift but at 4.20 m offers almost a metre extra in working height.

With no batteries (to charge and look after) and no hydraulic oil, the EcoLift is truly an Eco friendly solution.

### Typical applications and uses:

1st & 2nd Fix. Pipe Work, M & E. FM.  
Cleaning. Painting. Retail. Point of Sale. FM.

### Key Features

- Intuitive to operate - turn handle to elevate
- Patented\* lift mechanism, no power required
- Lightweight, easy to manoeuvre
- Small foot print (1.28 m x 0.74 m)
- Unlimited lift cycles, can be used 24/7
- Robust design for years of trouble free service
- Minimal operational costs, virtually maintenance free

### **PUSH AROUND - Self Powered**

Indoor Use

**Working Height:** 4.20 m

**Applications:** 1st & 2nd fix.  
Pipe Work, M&E. F.M. Cleaning.  
Painting. Point of Sale. Retail.



# Model ECOLIFT

LOW-LEVEL ACCESS

## Specifications

### WORKING DIMENSIONS

Maximum working height:	4.20 m
Maximum platform height:	2.20 m
Basket dimensions:	0.85 m (L) x 0.64 m (W)
Working foot print:	1.28 m x 0.74 m
Safe working load - platform:	150 kg (1 person + tools)
Maximum manual force:	200N
Maximum gradient for operation:	0.5 degrees
Maximum wind force:	Internal use only 0 m/s
Maximum castor point load:	155 kg (1.52kN)
Maximum wheel force:	155 kg (1.52kN)
Power Sound Level:	less than 70dBa

### CLOSED DIMENSIONS

Length:	1.28 m
Width:	0.74 m
Height:	1.95 m
Weight:	305 kg

### LIFT CYCLES

Unlimited

## Safety features

- 'Auto-lok' brake on elevation
- Elevates only when operated
- Lifting mechanism interlocked



## IMPORTANT

JLG is continually researching and developing products and reserves the right to make modifications without prior notice. All data in this document is indicative. Certain options or country standards will increase weight. Specifications may change to meet country standards or with the addition of optional equipment.

Due to continuous product improvements, JLG Industries reserves the right to make specification and/or equipment changes without prior notification.



## JLG EMEA BV

Polaris Avenue 63  
2132 JH Hoofddorp  
The Netherlands  
Tel.: +31 (0)23 565 5665  
[www.jlg.com](http://www.jlg.com)  
[www.powertowers.com](http://www.powertowers.com)

An Oshkosh Corporation Company